

MACHINE FOR ROLLER BLINDS



TR 2000

Roller blinds cutting and squaring table specifically designed for the production of high quality products. It is a table of considerable size that allows the double possibility to cut with cold or with ultrasonic. The type of cutting is input by a "touch-screen panel".



Touch screen computer



Roll holder



Checking and measuring fabrics square

FEATURES:

- A touch screen computer allows to set and memorize all fabric information such as speed and types of cut (cold or ultrasonic cut).
- Two reel-holding rollers with automatic fabric unrolling and aligning by means of a photocell.(**on request**)
- Pneumatic fabric pressure unit during the cutting phase.
- The fabric runs on a luminous check panel located on the working table allowing the operator to check fabric quality.(**on request**)
- Abutment bar whit manual handling.(**on request**)
- Ultrasonic cutting head
- Crush cutting system
- All automatisms are controlled by a micro processor checking the functioning of all electronic and pneumatic components
- Emergency buttons
- All mechanic, electronic and pneumatic parts are guaranteed by UNI norms
- Machine TR 2000 has been built and designed according to CE norms
- On demand, TR 2000 can be supplied with cutting-dimensions and working-table sizes different from standard ones.

DIMENSIONS AND WEIGHT

- Length 4800 mm
- Height 1500 mm
- Width 4800 mm
- Weight 1050 Kg.

TECHNICAL SPECIFICATIONS

- Usefull cutting width: up to 3500mm
- Usefull cutting length: up to 4000mm
- Electric supply 220 V – 50/60 HZ
- Average electric consumption: 2 KVA
- Air supply : 6 BAR
- Average air consumption: about 30 lt/min